

(12) **United States Patent**
Seki et al.

(10) **Patent No.:** **US 6,978,087 B2**
(45) **Date of Patent:** **Dec. 20, 2005**

(54) **CAMERA HAVING DISPLAY DEVICE**

(75) Inventors: **Reiji Seki**, Tondabayashi (JP); **Makoto Akesaka**, Sakai (JP); **Hiroaki Minami**, Sakai (JP); **Tatsuya Suzuki**, Kawachinagano (JP); **Reiko Yoshida**, Sakai (JP); **Masami Ohyama**, Habikino (JP); **Hirofusa Kondo**, Ikeda (JP)

(73) Assignee: **Minolta Co., Ltd.**, Osaka (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/870,950**

(22) Filed: **Jun. 21, 2004**

(65) **Prior Publication Data**

US 2004/0223067 A1 Nov. 11, 2004

Related U.S. Application Data

(62) Division of application No. 09/935,765, filed on Aug. 24, 2001, now Pat. No. 6,760,548.

(30) **Foreign Application Priority Data**

Aug. 24, 2000 (JP) 2000-253837

(51) **Int. Cl.⁷** **G03B 17/18**

(52) **U.S. Cl.** **396/50; 396/287; 396/296**

(58) **Field of Search** 396/48, 50, 287, 396/296; 348/333.02

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,492,450 A * 1/1985 Watanabe et al. 396/48

5,136,327 A	8/1992	Ogawa
5,485,238 A	1/1996	Miura et al.
5,585,878 A	12/1996	Matsukawa
5,608,491 A	3/1997	Sasagaki et al.
5,640,627 A	6/1997	Nakano et al.
5,678,092 A	10/1997	Kim et al.
5,745,810 A	4/1998	Matsushima
6,016,407 A	1/2000	Tsukahara
6,072,960 A	6/2000	Goto et al.
6,128,446 A	10/2000	Schrock et al.
6,222,538 B1	4/2001	Anderson
6,341,201 B1	1/2002	Ishiguro et al.

FOREIGN PATENT DOCUMENTS

JP	9-105998	4/1997
JP	11-282074	10/1999

* cited by examiner

Primary Examiner—W. B. Perkey

(74) *Attorney, Agent, or Firm*—McDermott Will & Emery LLP

(57) **ABSTRACT**

A disclosed photographing apparatus has a LCD display, a select member, and a controller. The display displays information about a photographic condition, in arbitrary display form using a dot-matrix. The select member selects one display mode among a plurality of display modes. In each mode of the plurality of display modes, display forms are different to each other, standard information required for photographing is displayed common to every display mode, and at least one information inherent to each display mode is displayed. The controller controls the display to display the display mode selected by the selector, and at a time of starting the camera, to display a display mode which has been displayed when the camera was previously switched off.

13 Claims, 16 Drawing Sheets

